

M7Xi / M8Xi

Long-range scope with 34 mm tube increases strength and reliability and provides greater elevation and windage adjustments for longer ranges.



M7Xi 4-28X56



BLACK, (WITHOUT ELECTRONICS)

Dimensions (approx.)*
387 mm (15.2 in.) length
950 g (33.5 oz.) weight

Magnification	Eye Relief	Diopter Adjustment	Parallax Adjustment	Elevation Range @ 100 m	Windage Range @ 100	Wind/Elevation Click Value
4 - 28x	90 mm (3.54 in.)	-2 to +2	Side Focus	260 cm / 26,0 mils	± 60 cm / 6,0 mils	1 cm (0.1 mrad)
Objective Lens	Tube diameter	Field of View at 100 m	Operating Temperature	Immersion	Nitrogen Filling	Battery
56 mm (2.2 in.)	34 mm (1.35 in.)	9,0 - 1,42 m	according to MIL STD 810G	20 m (21.8 y)	yes	1 x CR2032



M8Xi 1-8X24

BLACK, (WITHOUT ELECTRONICS)

Dimensions (approx.)*
274 mm (10.8 in.) length
750 g (26.5 oz.) weight

Magnification	Eye Relief	Diopter Adjustment	Parallax Adjustment	Elevation Range @ 100 m	Windage Range @ 100	Wind/Elevation Click Value
1 - 8x	90 mm (3.54 in.)	-2 to +2	Side Focus	260 cm / 26,0 mils	± 60 cm / 6,0 mils	1 cm (0.1 mrad)
Objective Lens	Tube diameter	Field of View at 100 m	Operating Temperature	Immersion	Nitrogen Filling	Battery
24 mm (0.94 in.)	34 mm (1.35 in.)	32,0 - 4,5 m	according to MIL STD 810G	20 m (21.8 y)	yes	1 x CR2032



All products are available on request with locking turrets and tactile clicks - Specifications subject to change without notice.
*Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.