

M5Xi 5-25X56

Long-range scope with 34 mm tube, true 25x magnification, etched glass G2B Mil-Dot, MSR, B4I, H59 or Tremor 3 reticle, DuoScale™ elevation with second-rotation scale that's hidden when inactive.



APPLICATIONS:

Standard issue Rifle scope for Military & Law Enforcement

- **ONE-PIECE 34MM TUBE** increases strength and reliability and provides greater elevation and windage adjustments for longer ranges.
- **BROADBAND ANTI-REFLECTION COATINGS** for 94% + light transmission to ensure optimal performance in low light.
- **OPTIMIZED EXTERIOR DESIGN** with larger, positive grip elevation, windage, parallax and illumination knobs and nonslip diopter and magnification adjustment.
- **ILLUMINATED RETICLE** with seven night and four day levels with two "OFF" positions at each end, and quick standby levels between each for fast return setting.
- **OPTIMIZED TUBE AND KNOB CONFIGURATION** for more mounting options and optimum performance with different rifles and added equipment.
- **PRECISE WINDAGE/ELEVATION ADJUSTMENT** is easy and accurate for repeated accuracy, with tactile click-by-click feedback you can hear and feel.
- **WATERPROOF/FOGPROOF** durable construction you can trust to stand up to any cold or wet condition. Waterproof to depths of 10 meters (33 feet).
- **SHOCKPROOF** and rugged enough to withstand impact testing to 900 Gs on all optical and electronic components.

M5Xi 5-25X56



BLACK, CW

Dimensions (approx.)*
420 mm (16.6 in.) length
34 mm Tube Diameter

- ITEM NUMBER 8704-G2B
- ITEM NUMBER 8704-MSR
- ITEM NUMBER 8704-H59
- ITEM NUMBER 8704-T3
- ITEM NUMBER 8704-B4I-2BE


M5Xi 5-25X56




COYOTE BROWN, CW

Dimensions (approx.)*
420 mm (16.6 in.) length
34 mm Tube Diameter

- ITEM NUMBER 8709-G2B
- ITEM NUMBER 8709-MSR
- ITEM NUMBER 8709-H59
- ITEM NUMBER 8709-T3




MSR RETICLE SUBTENSIONS




G2B MILDOT RETICLE SUBTENSIONS



B4I RETICLE SUBTENSIONS



HORUS 59 RETICLE SUBTENSIONS



HORUS TREMOR 3 RETICLE SUBTENSIONS

Magnification	Objective Lens	Eye Relief	Dioptic Range	Field of View at 100 m	Wind/Elevation Click Value	Windage Range at 100	Elevation Range at 100 m	Parallax/Focus	Adjustment Knobs	Battery
5-25x	56 mm	90 mm	-2 to +3	7-14 m	1 cm (0.1 mrad)	+/- 60 cm (6 mils)	260 cm (26 mils)	Side Focus	100% Sealed	CR2450
Weight	Waterproof	Exit Pupil	Temperature Range	Elevation Adjustment Knob	Illumination Control	Focal Plane	Parallax/Focus Range	Turret Direction	Lens Cap	Reticle
1,000 g (36.3 oz.)	Submersion to 10m (33ft.)	9.8 - 2.2 mm	-25°C to +63°C (-13°F to +145°F)	DuoScale™ / Resettable Zero	Rotary Digital Control with Intermediate Standby	1st 2nd (B4I 2BE)	50 m to Infinity	Clockwise or Counter Clockwise	Yes	G2B, MSR, H59, TReMoR3, B4I 2BE

Specifications subject to change without notice.

*Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.