

T1028

STEINER 
Nothing Escapes You

10x magnification for more power and performance without sacrificing weight or adding bulk to your field gear.



10X28 T1028

Dimensions (approx.)*
129.5 x 116.8 x 48.3 mm
(5.1 x 4.6 x 1.9 in.)

ITEM NUMBER 2004

APPLICATIONS:

Standard issue Binocular
for Military & Law Enforcement

- **HIGH DEFINITION OPTICS** are specially coated for the highest light transmission, sharp edge-to-edge views and contrast, even in low light.
- **ROOF PRISM DESIGN** is extremely light weight, compact and streamlined, easy to pack, carry, hold and use.
- **TWO-WAY-VALVE-SYSTEM** seals pressurized dry nitrogen into the optic, for fogproof clarity in any condition from arctic cold to desert heat.
- **FAST-CLOSE-FOCUS™** central focusing wheel requires minimal rotation for quick, absolute sharpness from close up to infinity.
- **MILITARY GRADE RUBBER ARMORING** protects chassis and lenses, reduces noise and provides a sure grip in all conditions.
- **CLICLOC® SYSTEM** attaches and releases neck strap or harness instantly with push button ease and designed so binoculars hang straight and action-ready.

Magnification	Focus System	Optics Systems	Close Focus	Objective Lens	Exit Pupil	Luminosity	Twilight Factor	Field of View @ 1,000 m	Field of View Angular	Dioptric Range	Interpupillary Distance
10x	Fast-Close-Focus™	High Definition	1.8 m (6 ft.)	28 mm	2.8 mm	7.1	17.1	≥ 88 m	6°	± 4 dpt	56 - 74 mm
Weight	Waterproof	Temperature Range	Eye Relief	Resolving Power	Rubbing Armoring	Eyecups	Neck Strap	Neck Strap Attachment	Objective Cover	Rain Protection Cap	Carry Case
360 g (12.7 oz.)	Submersion to 1.8 m (6 ft.)	-20°C to +70°C (-4°F to +158°F)	16 mm	≤ 6"	NBR Long Life	Ergonomic	Neoprene	ClicLoc®	Yes	Yes	Gear Bag

Specifications subject to change without notice.

*Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.