

# CQBL-1

## CLOSE QUARTER BATTLE LASER

ONE OF THE SMALLEST AND MOST RUGGED DUAL-FUNCTION LASERS AVAILABLE, THE CQBL-1 IS COMPATIBLE WITH VIRTUALLY EVERY SUBMACHINE GUN AND SHORT-BARREL RIFLE THERE IS; RUGGED AND DURABLE FOR USE ON CARBINE, RIFLE AND LIGHT MACHINE GUN SYSTEMS.

### OVERALL FEATURES

- Co-aligned visible red aiming laser and IR aiming laser
- Integrated push-button switch and remote cable pressure-pad switch activation - tap and release for momentary activation; tap twice for 5-minute continuous ON
- Dual function/single power mode
- Integrated Picatinny mount
- Remote cable port



Available in **black** (60603) and **flat dark earth** (60603E)



**Co-aligned Visible and IR Lasers** eliminate the need to sight in each laser individually



**Low-profile windage and elevation adjusters** ensure a constant zero



**Low profile** for mounting in front of scopes, holographic or NV Sights

eOptics

**STEINER**   
Nothing Escapes You

# ..... CQBL-1 | CLOSE QUARTER BATTLE LASER .....



## SPECIFICATIONS

### Close Quarter Battle Laser

		CQBL-1 60603/ 60603E
LASER TYPE	Visible Red or Green	Red - Class 3R
	IR Laser Pointer	Class I
	IR Laser Illuminator	-
POWER OUTPUT	Visible Red / Green Laser	<5 mW
	IR Laser Pointer	<0.7 mW
	IR Laser Illuminator	-
WAVELENGTH	White Light	-
	Visible Red Laser	635 nm +/-3%
	Visible Green Laser	-
PEAK ILLUMINANCE	IR Laser Pointer	850 nm +/-3%
	IR Laser Illuminator	-
	White Light	-
BEAM DIVERGENCE	Visible Laser	<0.8 mrad
	IR Laser Pointer	<0.8mrad
	IR Laser Illuminator	-
RANGE/VISIBILITY (NIGHT/DAY)* <small>Range may vary depending on light conditions</small>	White Light	-
	Visible Red Laser	250 m
	Visible Green Laser	-
Temperature	IR Laser Pointer	250 m
	IR Laser Illuminator	-
	White Light	-
Battery Life (Mode Dependent)	Temperature	-40°C to +65°C
	Battery	CR123A
	Material	Aircraft Aluminum
Weight (with Battery)	Color	Black, FDE
	Dimensions (LxWxH)	5.6 oz / 159 g
		4.0 x 1.5 x 1.1 in.
Waterproof		10.2 x 3.8 x 2.5 cm
	Mount	Submersible to 5m
	Windage & Elevation Adjustment	Integrated Picatinny
Activation Switch		Yes
	Remote Cable Pressure Pad	Integrated Push Button
		Yes

**STEINER**   
Nothing Escapes You

Steiner eOptics, Inc.  
3475 Newmark Drive  
Miamisburg, OH 45342, USA  
Tel: (937) 426-2341  
[www.steiner-defense.com](http://www.steiner-defense.com)

\*The figures in the table are for guidance only. Range performance will vary depending on ambient light level, atmospheric conditions, target reflectivity, and imaging system performance. These figures are a composite of tests using the highest power settings performed on a variety of occasions. IR tests used a PVS-14 in starlight with no moon or urban lighting. Visible laser tests were performed in daylight under a variety of lighting conditions